



Dimensions / Weight	
Dimensions H x W x D	151 x 74 x 55 cm
Weight	750 kg
Flue connexion	top
Center back connexion	- cm
Center to back top connection	21 cm
Center external air connection	20,8 cm
Flue pipe Ø	150 mm
Fresh air pipe Ø	100 mm
Minimum clearance to combustibles rear/side/front	20/30/80 cm
Dimensions window fireroom	51 x 36 cm
Fuel	firewood
Log length	30 cm
Pellet quantity	-



Performances	
Energy efficiency	77,3 %
Energy class	A+
Nominal heat output	7,1 kW
Min-Max heat output	3-8,5 kW
Heating capacity	45-180 m <sup>3</sup>
Wood load / h	2,08 kg
Flue draft	12 Pa
Flue gas temp. at nominal heat output	210 ° C
Gas flow	10,2 g/s

Emission of combustion products	
CO % (at 13 % O <sub>2</sub> )	0,06
CO mg/Nm <sup>3</sup>	716
Nox mg/Nm <sup>3</sup>	107
VOC mg/Nm <sup>3</sup>	29
Dust mg/Nm <sup>3</sup>	38
Test standard	EN 13240
Test report number	EZKA/2021-07-00014-1
Date	11/1/2021

Dimensions / Weight	
Dimensions H x W x D	191 x 74 x 55 cm
Weight	886 kg
Flue connexion	top
Center back connexion	- cm
Center to back top connection	21 cm
Center external air connection	20,8 cm
Flue pipe Ø	150 mm
Fresh air pipe Ø	100 mm
Minimum clearance to combustibles rear/side/front	20/30/80 cm
Dimensions window fireroom	51 x 36 cm
Fuel	firewood
Log length	30 cm
Pellet quantity	-



Performances	
Energy efficiency	77,3 %
Energy class	A+
Nominal heat output	7,1 kW
Min-Max heat output	3-8,5 kW
Heating capacity	45-180 m <sup>3</sup>
Wood load / h	2,08 kg
Flue draft	12 Pa
Flue gas temp. at nominal heat output	210 ° C
Gas flow	10,2 g/s

Emission of combustion products	
CO % (at 13 % O <sub>2</sub> )	0,06
CO mg/Nm <sup>3</sup>	716
Nox mg/Nm <sup>3</sup>	107
VOC mg/Nm <sup>3</sup>	29
Dust mg/Nm <sup>3</sup>	38
Test standard	EN 13240
Test report number	EZKA/2021-07-00014-1
Date	11/1/2021